

Wyse® V10L Thin Client

WYSE
| | | |

Fact sheet



Designed to Perform in Data-driven Environments.

The Wyse® Thin OS™ powered Wyse V10L thin computer delivers the performance you need; dual-video support (with purchase of optional monitor splitter cable); 128MB Flash, 128MB DDR RAM; plus serial, parallel, and USB ports.

Using the same form-factor as the Wyse V class family of thin computers, the Wyse V10L thin computer can fit easily into most work environments.

At a glance:

User Experience

- Fast and responsive performance
- Simple and fast to install, connect, and use out of the box
- No motors results in lower power consumption, quiet operation, and ultra-high reliability
- ICA version 10.x compatibility
- Built-in support for Wyse TCX virtualization technologies

Enterprise Security

- No data is stored on the thin client, so it cannot be lost or stolen
- Smart card support

Connectivity

- Connects to two monitors simultaneously (requires optional splitter cable)
- 3 USB ports
- Fast LAN access

Management

- Automatic configuration and updating via DHCP options and FTP
- Integrates with Wyse Device Manager for minimal day-to-day on-going support and remote monitoring

Wyse V10L Thin Client

Specifications

Processor	Via C7 Eden 800MHz
Memory	128MB Flash/128MB DDR RAM
I/O peripheral support	One DVI-I Port One DVI-I Port to VGA (DB-15) Adapter Dual-video Support with: Optional DVI-I to DVI-D plus VGA-monitor splitter cable (sold separately) Enhanced USB keyboard with PS/2 mouse port and Windows keys PS/2 mouse included One serial port One parallel port Three USB 2.0 ports (1 on front, 2 on back)
Networking	10/100 Base-T Fast Ethernet port (RJ-45) Optional external USB 802.11b/g wireless adapter
Display	VESA monitor support with Display Data Control (DDC) for automatic setting of resolution and refresh rate Single Monitor at 32-bit color or 24-bit color: up to 1920x1200@60Hz Dual Monitors used simultaneously (requires optional monitor splitter cable): up to 1280x1024x32bpp@60Hz
Audio	Output: 1/8-inch mini, full 16-bit stereo, 48KHz sample rate Input: 1/8-inch, 8-bit mini microphone
Options	Internal Smart Card reader Internal wireless
Physical characteristics	Height: 7.9" (201mm) Width: 1.8" (46mm) Depth: 7.1" (180mm) Shipping Weight: 8 lbs. (3.6kg)
Mountings	Vertical foot (optional horizontal feet) Optional VESA mounting bracket Built-in Kensington security slot (cable sold separately)
Power	Worldwide auto-sensing 100-240 VAC, 50/60 Hz Average power usage with device connected to 1 keyboard with 1 PS/2 mouse and 1 monitor: 17.2 Watts
Temperature Range	Horizontal position: 50° to 95° F (10° to 35° C) Vertical position: 50° to 104° F (10° to 40° C)
Security	Kensington lock slot
Safety Certifications	German EKI-ITB 2000, ISO 9241-3/-8 cULus 60950, TÜV-GS, EN 60950 FCC Class B, CE, VCCI, C-Tick WEEE, RoHS Compliant
Warranty	Three-year limited warranty

Wyse Technology Inc.
3471 North First Street
San Jose, CA 95134-1801

Visit our website at:
<http://www.wyse.com>
Or send email to:
sales@wyse.com

Wyse Sales
800 GET WYSE
(800 438 9973)

Wyse Customer Service Center:
800 800 WYSE
(800 800 9973)

WYSE
| | | |

Wyse V10L Thin Client



Wyse Technology Inc.
3471 North First Street
San Jose, CA 95134-1801

Visit our website at:
<http://www.wyse.com>
Or send email to:
sales@wyse.com

Wyse Sales
800 GET WYSE
(800 438 9973)

**Wyse Customer
Service Center:**
800 800 WYSE
(800 800 9973)

WYSE
| | | |